



Product Specification Sheet

PATTERN: DECK

PRODUCT DESCRIPTION

MARINE FLOORING 54"

GENERAL

TOTAL WT - OZ/SQ YD (CFFA-700D)	24.3
TOTAL WT - OZ/LIN YD (CFFA-700D)	36
WIDTH - INCH (MIN) (CFFA-700A)	54
TOPSKIN THICKNESS (MILS)	19.8
FACE CONTENT	PVC

SUBSTRATE

CONSTRUCTION	WOVEN
WEIGHT OZ/SQ YD	2.58
CONTENT	100% PET
FIBER TYPE (FILAMENT/SPUN)	SPUN

ADHESION (CFFA-3)	WARP	5
POUNDS/INCHES (MIN)	FILL	5
TENSILE STRENGTH (CFFA-17)	WARP	130.5
POUNDS (MIN)	FILL	95.5
ELONGATION @ 15# (CFFA-17)	WARP	2%
% (MIN)	FILL	2%
TRAP TEAR STRENGTH (CFFA-14)	WARP	15
POUNDS	FILL	11.9
TACK STRENGTH (STITCH) (CFFA-14)	WARP	81.2
POUNDS (MIN)	FILL	70.8
ABRASION (CFFA-1A)		
WYZENBEEK - WIRE SCREEN	NO CHANGES @ 6000 CYCLES	
BLOCKING (CFFA-4)	NO. 1	
W-FLEX (CFFA-10)	PASS	
CROCK (CFFA-7)	PASS	
UV (CFFA-2)	QUV (HOURS) - OUTDOOR	650 HOURS
MILDEW RESISTANCE - ASTM G-21	PASS	
LAMINTATED (WOOD)	YES	
APPLICATION - INDOOR/OUTDOOR	OUTDOOR	
	FINISH TYPE	CLEAR VINYL
CALIFORNIA TECH. BULLETIN 117	PASS	
UFAC FABRIC, CLASS 1	PASS	

Terms and corresponding data refer to performance in the specific test indicated and should not be construed to imply the behaviour of this or any other material under actual conditions. This information is accurate to the best of our knowledge at the time of printing, but is not intended to relieve the user from its responsibility to comply with all procedures applicable to the safe use of this product.